CIR375-GN-D

5-Port Industrial GPS 4G LTE Router



- 1×WAN port, 1×WAN/LAN port, 3×LAN ports, 1×RS232, 1×RS485
- Support 2G/3G/4G network all over the world, support APN/VPDN sim card
- Support multiple network management methods, including SSH, WEB, TELNET and a network management platform
- Support GPS positioning
- Support dual SIM card redundancy
- Industrial-grade design with IP30 sheet metal enclosure
- Operating temperature range -40°C to +75°C

Product Description

CIR375-GN-D is a flagship industrial router with 5 network ports, built with a high-end Qualcomm CPU solution in the industry. It integrates multiple hardware interfaces, including: 5 network ports (1WAN + 1×WAN/LAN + 3×LAN), dual serial ports (1×RS232 + 1×RS485), enhanced Qualcomm Wi-Fi, GNSS positioning, and dual external card slots. Users can quickly build their own application networks with it.

Designed for harsh industrial environments, with industrial-grade standards: wide temp.-40°C~75°C, DC 9~48V power, EMC 3B protection. Rigorously tested, built-in dual watchdog & self-recovery, reliable across industries. This product is widely used in scenarios such as meteorological monitoring systems, store cash register monitoring systems, energy storage power station systems, agricultural environment monitoring systems, and smart water affairs systems

Product Features

- Industrial grade design, wide temperature -40°C ~75°C, sheet metal housing, IP30 protection
- Support horizontal desktop placement, wall hanging and rail installation
- Wide voltage DC9~48V input, with power reverse protection
- Multiple hardware protection such as static electricity, surge and electric fast pulse group
- Provide 4Gnetwork system
- Cellular network theoretical rate: Download: 150Mbps / Uplink: 50Mbps
- Support automatic network inspection, 4G/3G/2G mode switching, support APN/VPDN private network card
- Support dual SIM card redundancy
- Support 3LAN+1WAN/LAN+1WAN, 10/100Mbps rate
- Support TCP/UDP/Modbus TCP to Modbus RTU/MQTT data acquisition capability
- Support GNSS positioning services, and can report GPS/Beidou positioning data through WEB configuration and screening
- Support VPN (PPTP, L2TP, IPSec, OpenVPN, GRE) and VPN encryption function
- Support dynamic domain name (DDNS), PPPoE, DHCP, static IP functions
- Support access restrictions for firewalls, NAT, and black and white lists, and supports SNAT and DNAT


Technical Specifications

Cellular	Global Wide Band	TDD-LTE: Band 34/38/39/40/41 FDD-LTE: Band 1/2/3/4/5/7/8/12/13/18/19/20/25/26/28/66 WCDMA: B1/2/4/5/6/8/19 GSM: B2/3/5/8
	Theoretical Rate	Download: 150Mbps/Uplink: 50Mbps； Take the on-site measurement as the standard
	Antenna Interface	1×Standard SMA-K antenna interface (outer screw inner hole)
	Sim Card Slot	2×Nano-SIM
Wi-Fi	Standard	IEEE 802.11b/g/n, 2.4GHz, AP/STA/ bridge
	Theoretical Rate	300Mbps, the actual rate of WIFI is subject to the interference factors of the field environment
	Antenna Interface	2×Standard SMA-K antenna interface (external thread and internal hole)
	MIMO	2×2
	Transmission Distance	The open area is 500m, and the actual transmission distance depends on the field environment
Ethernet	Number Of Network Ports	1WAN+1WAN/LAN+3LAN
	Network Port Specifications	RJ45 interface: 10/100 Mbps adaptive, in line with IEEE 802.3, with 1.5KV network isolation transformer protection
DTU	DTU Mode	TCP/UDP/Modbus TCP to RTU/MQTT/HTTPD/AWS/ALI Pass-Through/Modbus RTU
	Heartbeat Packet/ Registration Packet	√
	Baud Rate	1200, 2400, 4800, 9600, 19200, 38400, 57600, 115200, 230400
	Data Bit	7, 8
	Stop Bit	1, 2
	Check Bi	NONE, ODD, EVEN
	Serial Port Type	1×RS485+1×RS232
GNSS	Antenna Interface	1×SMA-K (external thread and internal hole)
	Antenna Specifications	Square antenna, frequency range 1575.42MHz, signal strength 3.5 DBI, standard size 3 meters
	Location Mode	GPS data can be selected and reported
	PWR	The power indicator light is on after power on

Indicator Light	WiFi	It lights up when WIFI is on
	NET	4G-Green 3G-Orange 2G-Red
	SIG	Strong signal-Green Medium signal-Orange Weak signal-Red
Power	Adapter	DC 12V/1A
	Power Supply Interface	2P power terminal with reverse polarity protection
	Power Supply Range	DC 9-48V
	Working Current	<500mA@12V
Physical Characteristics	Hull	Sheet metal shell, dustproof grade IP30
	Size	110.0×85.0×30.0
	Way To Install	Guide installation, wall hanging installation, horizontal desk placement
	EMC	Level 3
	Working Temperature	-40°C~+75°C
	Storage Temperature	-40°C~+85°C (No condensation)
	Working Humidity	5%~95% (No condensation)
Software	VPN	PPTP, L2TP, IPSec, OpenVPN, GRE
Other	Reload	Support restore factory
	TBD	Debugging interface
	Ground Protection	Grounding screws

Dimensions

Unit: mm (first angle projection)



Ordering Information

Standard Model	RJ45 Port	RS232	RS485	Input Voltage
CIR375-GN-D	5	1	1	DC 9~48V

Contact Us

COME-STAR COMMUNICATION(WUHAN) CO., LTD.

Address: Building 4, East Area, Wuhan Innocenter, No.27 Yangqiaohu Avenue, Jiangxia District, Wuhan, China

Tel: +86-027-59257958

Mail: sales@come-star.com

Official site: www.come-star.com

Copyright © Come-Star All rights reserved